



Terminal



SIGNAL DIRECTION



Bi-Directional

SPEAKER CABLES

RATTLE SNAKE 3 M

2X 3.0 MM²

MSRP (19%): 15.99

High-quality and particularly flexible stereo loudspeaker cable for connecting amplifiers and power amplifiers to loudspeaker boxes. This loudspeaker cable is suitable for amplifier performances of up to around 250 watts of power per amplifier channel. The cable is manufactured from three stranded strings of oxygen-free copper (OFC) and three stranded strings of silver-plated oxygen-free copper (SPC). The proportion of silver-plated conductors means that this special design considerably improves transmission properties, particularly in the treble/mid-tone range! This Oehlbach cable's outer sheath is made from a tough and very flexible mix of plastics.

» 250 W

OFC
OXYGEN-FREE
COPPER

SPOFC
SILVER-PLATED
COPPER

Packaging size	200mm / 220mm / 220mm
Colour	Crystal clear
Weight (net)	90 g
Inner conductor material	OFC - oxygen-free copper , SPC/OFC - silver-plated oxygen-free copper
cable geometry	Round
cable cross section	2 x 3.0 mm ²
power max.	For amplifier performances of up to 250 watts
Features	Stereo speaker cable
Outer sheath material	plastic

item no.	Length	Color	EAN	MSRP (19%)
1085	100 m	Crystal clear	4003635010853	15.99 €

Item No. 1085



More information:

