



Jack  
Socket



SIGNAL DIRECTION



## RECEIVER AND TRANSMITTER FOR BLUETOOTH SIGNALS

**BTR 4.2 - REFURBISHED**

**MSRP (19%): 99.00**

Note: This product is certified B-goods. The goods have been inspected and are in a technically perfect condition. Visual defects on the packaging or on the product itself (scratches, discoloration) can not be excluded and do not constitute grounds for complaint.

Your right of withdrawal remains unaffected.

On all refurbished items you get full warranty of 2 years.

The Oehlbach BTR 4.2 Bluetooth transceiver inspires despite its compact format with a wide range of applications. The 2in1 adapter allows both sending and receiving audio signals, wirelessly via Bluetooth. Audio signals that are played in analog or via the optical digital input can be sent to compatible headphones or active speakers with the aid of the Bluetooth 4.2 protocol. In receiver mode, the BTR 4.2 accepts the Bluetooth signal from a mobile device or computer, and then outputs it via the transceiver's integrated 3.5mm jack interface. With support for aptX, Qualcomm True Wireless Stereo and an extremely low latency of under 40ms, the Oehlbach BTR 4.2 delivers outstanding acoustic performance in any situation.

**CERTIFIED  
REFURBISHED**



Qualcomm  
aptX



Qualcomm aptX  
Low Latency



Bluetooth

Qualcomm aptX and the aptX logos are owned by Qualcomm Technologies, Inc. and/or its subsidiaries. Use is granted. The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Oehlbach is under license. Other trademarks and trade names are those of their respective owners. The Qualcomm aptX - Low Latency Logo is owned by Qualcomm Technologies, Inc. and/or its subsidiaries. Use is granted.

Packaging size	60mm / 105mm / 190mm
Transmission standard	Bluetooth 4.2
Weight (net)	230 g
Colour	White
Housing material	More than five Inputs
Scope of delivery	Bluetooth transmitter/receiver, user manual, power supply, USB cable, Toslink cable, Toslink adapter
Air humidity range	5 bis 90 %
Sampling rate	48 kHz
Operating elements	Receiver/transmitter selector switch
Input voltage	5 V
Input power	5 W
Input current	1 A

Item No. D2C6078



More information:





item no.	Color	EAN	MSRP (19%)
D2C6078	White	4003635250006	99.00 €

Item No. D2C6078



More information:

