


AUDIO
EQUIP
PERFORMANCE



Terminal


SIGNAL DIRECTION
 Bi-Directional

SPEAKER CABLES

SPEAKER WIRE SP-7

2 X 0.75 MM²

Excellently made stereo loudspeaker cable wound on to a mini coil. This loudspeaker cable is suitable for amplifier performances of up to around 70 watts of power per amplifier channel. The use of oxygen-free copper (OFC) as the conducting material ensures that an extremely clear and true-to-life sound can be achieved with this loudspeaker cable. The cable has also been made from very many ultrathin stranded copper wires – each individual wire possesses a cross-section of around 0.20 mm. This complex design means that the cable is particularly conductive and flexible throughout.

70 W **OFC** **30 YEAR**
OXYGEN FREE COPPER **GUARANTEE**

Bending radius	10 mm
Inner conductor material	OFC - oxygen-free copper
cable geometry	Round
cable cross section	2 x 0.75 mm ²
Features	Stereo speaker cable , 30 years warranty, For amplifier performances of up to 70 watts
cable material	plastic

item no.	Length	Color	EAN	MSRP (19%)
201	10 m	transparent	4003635002018	15.99 €
202	20 m	transparent	4003635002025	29.99 €
205	30 m	transparent	4003635002056	41.99 €
206	10 m	White	4003635002063	15.99 €
207	20 m	White	4003635002070	29.99 €
208	30 m	White	4003635002087	41.99 €

